




SHOWN WITH SEC MILLENIUM SENSOR



SEC 3100 Digital Gas Transmitter

Features

- *Explosion Proof*
- *Back lighted LCD Display*
- *Low Cost*
- *Plug and play toxic, oxygen and combustible gas sensors*
- *Self-Check system*
- *4-20 mA output*
- *RS-485 Interface (Isolated)*
- *Alarm and fault relays*
- *Non-intrusive configuration*
- *Non-intrusive calibration*
- *Removable, non-volatile, time stamped data logging memory stick*
- *Optional IS barrier*
- *Digital communication link to SEC 3000, SEC 3300, SEC 5000 and SEC Millennium Gas Detectors*
- *Multi port housing for easy installation*

Applications

- *Petrochemical Refineries*
- *Compost Facilities*
- *Semi-Conductor Industry*
- *Mining*
- *Pulp and Paper Mills*
- *Oil Rig Platforms*
- *Buildings*
- *Automotive Industry*
- *Engine Test Rooms*
- *LNG & LPG Facilities*
- *Sewage Industry*
- *Water Treatment Plants*
- *Parking Garages*
- *Chemical Industry*
- *Nuclear Industry*
- *Fertilizer Industry*
- *Tunnels*
- *Medical Facilities*

Operation / Description


The SEC 3100 provides interface capabilities for any and all SEC gas detectors.

The SEC 3100 features:

- Back lighted LCD for Gas Level/Unit Parameter display
- Four (4) configurable Alarm/Fault Relays
- An isolated RS485 Modbus interface provides reliable communication in noisy environments and eliminates “Ground Loop” problems.
- Three magnetic switches for local configuration and calibration
- Time stamped data logging using a removable non-volatile memory module. Module can be removed from the unit to allow remote data downloading and data archiving.

An optional IS barrier allows “hot” sensor replacement in rated locations. This allows the user to install pre-calibrated/pre-configured sensor boards without removing unit power while maintaining EX rating. Removable circuit board stack and detachable connectors facilitate field-wiring installation.

SEC 3100 Digital Gas Transmitter



SPECIFICATIONS

Gas Sensor Compatibility

SEC 3000 & SEC 3300 Toxic Detector
SEC Millenium Infrared Detectors
SEC 5000 IREvolution Infrared Detectors

Output (digital)

RS-485 LAN (Isolated)

Output (optional relays)

4-20 mA (source type), max. 1000 ohm load at 24 VDC supply voltage

Display

Back Lighted LCD
LEDs for relay status

Operating Voltage

18-32 VDC

Operating Current (No Sensor)

314mA Max @ 24 VDC - All Options
w/Relays Only: 90mA Max @ 24V
100mA Max @ 18V
No Options: 50mA @ 24V
65mA Max @ 18V

Power Consumption SEC 3100 (No Sensor)

Nominal (no options, 24V): 1.2 W
Relays Option: Add 1 W
Heater option: Add 5.9 W

Ambient Temperature Range (Ta):

-50°C to +60°C (CUS)
-40°C to +70°C (IECEEx)

Humidity

0-99% RH (Non-condensing)

Housing Construction

Epoxy coated aluminum

Certification

CSA/NRTL: CI I, Div 1, Groups B,C,D T5
IECEEx: Ex d IIB + H2 T5 Gb

Housing Dimensions

5.25 (W) x 5.30 (L) x 4.95 (H) inches
{131 (W) x 132 (L) x 124 (H) mm}


Weight

Approximately 6 lbs. {2.8 Kg.}

Partial Gas List

Oxygen	(O2)	Carbon Monoxide	(CO)
Hydrogen	(H2)	Germane	(GeH4)
Ammonia	(NH3)	Silane	(SiH4)
Nitric Oxide	(NO)	Phosphine	(PH3)
Bromine	(Br2)	Sulfur Dioxide	(SO2)
Fluorine	(F2)	Nitrogen Dioxide	(NO2)
Arsine	(AsH3)	Chlorine Dioxide	(ClO2)
Ozone	(O3)	Hydrogen Sulfide	(H2S)
Chlorine	(Cl2)	Hydrogen Fluoride	(HF)
Phosgene	(COCl2)	Hydrogen Chloride	(HCl)
Diborane	(B2H6)	Hydrogen Cyanide	(HCN)
Formaldehyde	(HCHO)	Hydrogen Selenide	(H2Se)
Ethylene Oxide	(ETO)	Hydrogen Peroxide	(H2O2)
Combustible	(HC)	Carbon Dioxide	(CO2)

Current Output	Status
0.0 mA	Unit Fault
0.8 mA	Unit warm up
1.2 mA	Zero drift fault
1.6 mA	Calibration fault
2.0 mA	Unit spanning
2.2 mA	Unit zeroing
4-20 mA	Normal measuring mode
4.0 mA	Zero gas level
5.6 mA	10% Full Scale
8.0 mA	25% Full Scale
12 mA	50% Full Scale
16 mA	75% Full Scale
20 mA	Full scale
>20 mA	Over-range



SEC 3100 shown with SEC 3000 Sensor



Sensor Electronics Corporation

12730 Creek View Avenue, Savage, MN 55378 U.S.A. • (800) 285-3651 • (952) 938-9486 • FAX: (952) 938-9617
www.sensorelectronic.com • sales@sensorelectronic.com